

TECHNICAL DATA SHEET

AZAR GLOSS PAINT

INTRODUCTION

Azar Gloss is a synthetic high-gloss enamel paint that is easy to apply and has an excellent hiding power. Azar Gloss can be used on interior and exterior masonry surfaces.

APPLICATION

Before applying Azar Gloss, the surface should be cleaned properly to remove dust, loose particles, and fatty stains. The application of a suitable Azar primer is also crucial before applying the paint.

After priming, Azar Gloss should be diluted with up to 20 % Savana Turpentine or Azar Thinner, and applied onto the surface by means of a brush, a foam roller, or a spray gun.

FEATURES & BENEFITS

Azar Gloss is an alkyd-based synthetic enamel with a good alkyd content giving it an excellent gloss. Azar Gloss is also highly pigmented giving it a good hiding power.

COMPOSITION

Azar Gloss is based on synthetic enamel, pigments, organic and inorganic pigments, and additives. Azar Gloss is a 100% lead-free.

<u>Properties</u>	<u>Analysis</u>
Appearance	Wide variety of colors
Solid Content	60%
Density	1.08 g/L
Coverage	±10-12 m ² /Ltr. (according to porosity of surface)
Dilution	15 - 20 % with turpentine or thinner
Gloss	>80E @ 60E Angle
Drying Time	2 -3 hours and can be recoated overnight

STORAGE & PACKAGING

Azar Gloss should be stored at a temperature below 40EC. Azar Gloss containers should not be exposed to direct sunlight.

Azar Gloss is available in 1L, half gallon and one gallon metal containers.