



TECHNICAL DATA SHEET

1-IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY

Commercial product name: **AZARFIX**
Appearance: Milky White

2- TECHNICAL SPECIFICATIONS:

• Specific Gravity	-	1.1
• Solid content (25min at 150°C)	-	35+/-1%
• Viscosity Brookfield (25°C,sp.6,10rpm)		32000 -40000
• pH	-	8.5
• M.F.F.T.	-	14°C
• Particle size	-	0,5-3µm
• Film	-	transparent
• Emulsifier	-	Nonionic
• Adhesion	-	250-300 N/M2

3-DESCRIPTION

Azarfix is a homopolymer polyvinyl acetate stabilized with polyvinyl alcohol used in the production of adhesives and water based paints.

4-APPLICATIONS

Azarfix can be used for: Wood, Paper and Cartons

5-DRYING TIME

20 MINS

6-STORAGE

Keep the product in closed gallons/drums, between 5 and 30°C, in order to avoid water evaporation and skin formation on the surface. In case of skin formation, remove it, without agitating, before used. Under these conditions, the product can be kept one year without notable deterioration of his properties.

7-COMPATIBILITY

Compatible with all chemical products used in water based paints and adhesives

8-PACKAGING: 5KG